ULTRAVISION

PROFESSIONAL BOX CAMERA

BX-371UV

12V DC

12V DC/24V AC

Features

- Superb Wide Dynamic Range Performance
- BLC/HLC
- 650TVL
- 3D-DNR
- OSD Menu
- Superior night function (0.003 LUX)
- Motion detection & Privacy masking
- X10 digital zoom
- IR Cut Filter
- BLC/AGC/HLC

Specifications

MODEL	BX-371UV
Image Sensor	1/3" Sony CCD (PAL:ICX639BK/NTSC:ICX638BK)
DSP System	UltraVision DSP
Effective Pixels	PAL: 752(H)×582(V) / NTSC: 768(H)×494(V)
Scanning System	2 : 1 Interlace
O.S.D	Available
Sync. System	Internal/Line lock
Horizontal Resolution	**650TVL**
3D-DNR	Off/On(1~63 level adjustable)
S/N(Y Singal)	52dB(AGC OFF)
Lens mount	C/CS
Minimum Illumination	Color: 0.003(0.6)Lux(Sens-up OFF)/B/W: 0.0001(0.1)Lux(Sens-up OFF)
Privacy zone	On/Off(8Zone)
Sens-up	Auto/Fixed/Off(selectable limit ×2~×512)
Motion Detection	On/Off(8Zone, Alarm output)
Dynamic Range	52dB(×128)
Digital Zoom	On(×10)/Off
Electronic Shutter Speed	NTSC:1/60sec-1/120,000sec PAL:1/50sec-1/120,000sec
Backlight Compensation	WDR/BLC/OFF selectable
Gain Control	Low/Middle/High/Off selectable
D/N Selection	Color/Black&White/Auto/Exit
STABILIZER	On / Off
Mirror(H-REV)	On / Off
FLIP(V-REV)	On / Off
White Balance	ATW/AWC/Manual/Outdoor
Freeze	On / Off
SHARPNESS	On/Off(Level Adjutable)
Blemish compensation	64 Point(Even 32 point, ODD 32 point)
Iris Control	DC/Manual
Power	DC12±10% DC12(AC24/DC12 optional)
Dimension	122(L)×75(W)×65(H)mm
Weight	410g

Rear view

OSD Menu